

VENUS

Lighting & Electricals



2019

Best Selection for Comfort

Commercial, Industrial & Residential
Lighting & Electrical Materials

LED BULB


E27



Aesthetically designed Spherical LED Bulb for B22 & E27 lamp base.

- Input Voltage: AC 100-240V, 50/60Hz
- P.F ≥ 0.5 for
- High Surge Protection: 1.0 KV
- CRI: Ra>80
- LED Life: 25,000 BH
- ON/OFF 12,500
- Optics: Polycarbonate diffuser for better light distribution

Application areas



Wattage	Product Description	CCT	Lumen Output	Cut Out Dimension (mm)	Dimension (DxH) mm	Product Code
9W	LED Bulb	3000K	810lm	NA	60 x 108	VB130092760
	LED Bulb	6500K	810lm	NA	60 x 108	VB165092760
12W	LED Bulb	3000K	1080lm	NA	65 x 118	VB130122765
	LED Bulb	6500K	1080lm	NA	65 x 118	VB165122765
15W	LED Bulb	3000K	1350lm	NA	70 x 128	VB130152770
	LED Bulb	6500K	1350lm	NA	70 x 128	VB165152770



D = Diameter H = Height

LED BULB


B22



Aesthetically designed Spherical LED Bulb for B22 & E27 lamp base.

- Input Voltage: AC 100-240V, 50/60Hz
- P.F ≥ 0.5 for
- High Surge Protection: 1.0 KV
- CRI: Ra>80
- LED Life: 25,000 BH
- ON/OFF 12,500
- Optics: Polycarbonate diffuser for better light distribution

Application areas



Wattage	Product Description	CCT	Lumen Output	Cut Out Dimension (mm)	Dimension (DxH) mm	Product Code
9W	LED Bulb	3000K	810lm	NA	60 x 108	VB130092260
	LED Bulb	6500K	810lm	NA	60 x 108	VB165092260
12W	LED Bulb	3000K	1080lm	NA	65 x 118	VB130122265
	LED Bulb	6500K	1080lm	NA	65 x 118	VB165122265
15W	LED Bulb	3000K	1350lm	NA	70 x 128	VB130152270
	LED Bulb	6500K	1350lm	NA	70 x 128	VB165152270



D = Diameter H = Height

ECOTTA LED COB DOWN LIGHT

Recess mounted Circular type LED COB Down Light in Milky white finish with energy efficient electronic driver.

- Input Voltage: AC 85-265V, 50/60Hz
- Driver Type: Isolated
- Flicker Free
- High Surge Protection: 1.5 KV
- CRI: Ra>80
- LED Life: 50,000 BH

Application areas

General Shops Offices Reception Area
Restaurants Hospital Lobbies & Passages



Wattage	Product Description	CCT	Lumen Output	Cut Out Dimension (mm)	Dimension D(mm) H(mm)		P.F.	Product Code
10W	LED COB Down Light	3000K	900lm	Ø65	Ø90	52	0.5	VCB21301031-9
15W	LED COB Down Light	3000K	1350lm	Ø90	Ø115	65	0.5	VCB21301541-9
20W	LED COB Down Light	3000K	1800lm	Ø115	Ø140	76	0.5	VCB21302051-9

ECOTTA-PLUS LED COB DOWN LIGHT

Recess mounted Circular type multi CCT LED COB Down Light in Milky white finish with energy efficient electronic driver .


- Input Voltage: AC 85-265V, 50/60Hz
- Driver Type: Isolated
- Flicker Free
- High Surge Protection: 10W/15W/20W-1.5 KV, 30W/40W-2.5KV
- CRI: Ra>80
- LED Life: 50,000 BH

Application areas

General Shops Offices Reception Area
Restaurants Hospital Lobbies & Passages



D = Diameter H = Height



Wattage	Product Description	CCT	Lumen Output	Cut Out Dimension (mm)	Dimension A(mm) H(mm)		P.F.	Product Code
10W	LED COB Down Light	3000K	900lm	Ø65	Ø90	52	0.5	VCB216431031-9
	LED COB Down Light	4000K	1000lm	Ø65	Ø90	52	0.5	VCB216431031-9
	LED COB Down Light	6500K	900lm	Ø65	Ø90	52	0.5	VCB216431031-9
15W	LED COB Down Light	3000K	1350lm	Ø90	Ø115	65	0.5	VCB216431541-9
	LED COB Down Light	4000K	1500lm	Ø90	Ø115	65	0.5	VCB216431541-9
	LED COB Down Light	6500K	1350lm	Ø90	Ø115	65	0.5	VCB216431541-9
20W	LED COB Down Light	3000K	1800lm	Ø115	Ø140	76	0.5	VCB216432051-9
	LED COB Down Light	4000K	2000lm	Ø115	Ø114	76	0.5	VCB216432051-9
	LED COB Down Light	6500K	1800lm	Ø115	Ø114	76	0.5	VCB216432051-9
30W	LED COB Down Light	3000K	2700lm	Ø160	Ø200	108	0.95	VCB216433071-9
	LED COB Down Light	4000K	3000lm	Ø160	Ø200	108	0.95	VCB216433071-9
	LED COB Down Light	6500K	2700lm	Ø160	Ø200	108	0.95	VCB216433071-9
40W	LED COB Down Light	3000K	3600lm	Ø165	Ø230	120	0.95	VCB216434081-9
	LED COB Down Light	4000K	4000lm	Ø165	Ø230	120	0.95	VCB216434081-9
	LED COB Down Light	6500K	3600lm	Ø165	Ø230	120	0.95	VCB216434081-9




FLAPAN BASE LIGHT

Ultra slim edge lit type recess mounting LED luminaire with extruded aluminium housing, anti glare diffuser and separate energy efficient electronic driver.

- Input Voltage : AC85-265V, 50/60Hz
- High Performance electronic
- Driver Type: Isolated
- High Surge Protection : 2.5KV
- Power Factor: 0.95
- Average Life : 50000 hrs
- Flicker Free
- No harmful UV & IR radiations

Application areas

Corporate Offices Modern Workspaces
Banks Software Centres Hospitals



Wattage	Product Description	CCT	Lumen Output	Power Factor P.F.	Dimension (DxH) mm	Product Code	No. of Drivers
48W	LED Flapane Base Light	3000K	4320lm	0.95	595 x 595	VP213048221-9	1
	LED Flapane Base Light	4000K	4320lm	0.95	595 x 595	VP214048221-9	1
	LED Flapane Base Light	6500K	4320lm	0.95	595 x 595	VP216548221-9	1
60W	LED Flapane Base Light	6500K	5400lm	0.95	595 x 595	VP216560221-9	2
48W	LED Flapane Base Light	4000K	4320lm	0.95	295 x 1195	VP214048141-9	1
	LED Flapane Base Light	6500K	4320lm	0.95	295 x 1195	VP216548141-9	1



MARSLUX LED SMD FLOOD LIGHT

Broad Beam, High intensity LED SMD Flood Light with MCPET reflector, Die-Casted Aluminum Black Body.

- Input Voltage: AC 85-265V, 50/60Hz
- Driver Type: Isolated
- High Surge Protection: 4.0 KV
- CRI: Ra>70
- Power Factor 0.95
- IP 66
- LED Life: 50,000 BH


Application areas

Parking Areas Gardens Playing Areas

Stage Lighting Lighting of Sensitive Areas



Wattage	Product Description	CCT	Lumen Output	Dimension			P.F.	Product Code
				W(mm)	H(mm)	D(mm)		
30W	LED Marslux Flood Light	3000K	2700lm	195	165	40	0.95	VFL21303001-9B
	LED Marslux Flood Light	6500K	2700lm	195	165	40	0.95	VFL21653001-9B
50W	LED Marslux Flood Light	3000K	4500lm	230	195	57	0.95	VFL21305001-9B
	LED Marslux Flood Light	6500K	4500lm	230	195	57	0.95	VFL21655001-9B
100W	LED Marslux Flood Light	3000K	9000lm	297	250	57	0.95	VFL213010001-9B
	LED Marslux Flood Light	6500K	9000lm	297	250	57	0.95	VFL216510001-9B
150W	LED Marslux Flood Light	3000K	13500lm	355	290	57	0.95	VFL213015001-9B
	LED Marslux Flood Light	6500K	13500lm	355	290	57	0.95	VFL216515001-9B
200W	LED Marslux Flood Light	3000K	18000lm	428	328	65	0.95	VFL213020001-9B
	LED Marslux Flood Light	6500K	18000lm	428	328	65	0.95	VFL216520001-9B




LED URBINO Street Light

Aesthetically Designed LED Street Light, Powder Coated Aluminium Housing and Polycarbonate Lense

- Input Voltage : AC85-265V, 50/60Hz
- High Performance electronic
- Driver Type: Isolated
- High Surge Protection : 4KV
- Power Factor: 0.95
- Average Life : 50000 hrs

Application areas

- Compound Lighting
- Residential Buildings
- Gardens
- Pathways
- Street Lights



Wattage	Product Description	CCT	Lumen Output	Dimension			P.F.	Product Code
				A(mm)	B(mm)	H(mm)		
50W	LED Urbino Street Light	3000K	4500lm	540	195	60	0.95	VSL21305001-9B
	LED Urbino Street Light	6500K	4500lm	540	195	60	0.95	VSL21655001-9B
100W	LED Urbino Street Light	3000K	9000lm	700	245	90	0.95	VSL213010001-9B
	LED Urbino Street Light	6500K	9000lm	700	245	90	0.95	VSL216510001-9B
150W	LED Urbino Street Light	3000K	13500lm	772	280	90	0.95	VSL213015001-9B
	LED Urbino Street Light	6500K	13500lm	772	280	90	0.95	VSL216515001-9B

Contact: